




LANGOFLEX GT



LANGOFLEX GT



Mechanical & Abrasion Protection



Expandable Sleeving



Braided



PET .010" (0.25 mm) monofilament



Black



Low: -40°C (-40°F)
High: 150°C (302°F)



High abrasion resistance
Cold cutting (scissors,...)
End-fray resistance

PHYSICAL PROPERTIES

Physical properties	Spec	Value
Operating temperature	-	-40/150°C (-40/302°F)
Peak temperature	-	175°C (347°F)
Abrasion resistance	SAE ARP 1536	> 30 000 cycles
Flammability	FMVSS 302	self-extinguishing
Chemical resistance	Resists the majority of chemicals and automotive fluids	

DIMENSIONS

Designation	Nominal Ø		Maximum Ø (mm)	Ends (per carrier)
	(inches)	(mm)		
LANGOFLEX GT 1/4	1/4"	0.236	6	3
LANGOFLEX GT 5/16	5/16"	0.313	8	3
LANGOFLEX GT 3/8	3/8"	0.394	10	3
LANGOFLEX GT 1/2	1/2"	0.512	13	3
LANGOFLEX GT 3/4	3/4"	0.748	19	3
LANGOFLEX GT 1	1"	1.000	25	3
LANGOFLEX GT 1 1/4	1 1/4"	1.260	32	3
LANGOFLEX GT 1 3/4	1 3/4"	1.732	44	4

PACKAGING

Coils, Cut lengths upon request