


LANGOFLEX PET VO



LANGOFLEX PET VO



Mechanical & Abrasion Protection



Expandable Sleeving



Braided



PET .010" (0.25 mm) monofilament



Black



Low: -40°C (-40°F)
High: 150°C (302°F)



Mechanical and abrasion protection
Non-Flammable

PHYSICAL PROPERTIES

Physical properties	Spec	Value
Operating temperature	-	-40/150°C (-40/302°F)
Peak temperature	-	175°C (347°F)
Abrasion resistance	ISO 6722 LV 312-3	> 2 000 cycles
Flammability	UL 94 (raw material) FMVSS 302	V0 type A (non-flammable)
Chemical resistance	Resists the majority of chemicals and automotive fluids	

DIMENSIONS

Designation	Nominal Ø		Maximum Ø mm
	inches	mm	
LANGOFLEX PET V0 03	1/8"	3	6
LANGOFLEX PET V0 05	3/16"	5	9
LANGOFLEX PET V0 06	1/4"	6	9
LANGOFLEX PET V0 08	5/16"	8	11
LANGOFLEX PET V0 10	3/8"	10	13
LANGOFLEX PET V0 12	1/2"	12	17
LANGOFLEX PET V0 14	9/16"	14	22
LANGOFLEX PET V0 16	5/8"	16	25
LANGOFLEX PET V0 20	7/8"	20	27
LANGOFLEX PET V0 25	1"	25	34
LANGOFLEX PET V0 40	1 3/4"	40	51

PACKAGING

Coils, Cut lengths upon request