

NU-SLEEVE SG-200 HW



NU-SLEEVE SG-200 HW



Mechanical & Abrasion Protection
Thermal Protection



Uncoated & Coated Sleeving



Braided or knitted



Fiberglass
High temperature silicone rubber



Option: Black, red oxide
 Other colors upon request




Low: -60°C (-76°F)
High: 260°C (500°F)



Fireproof and waterproof protection
High thermal insulation
Heavy duty applications



 UZFT2 - VW1 Rating

NEMA TF1 - Type 5, SAE AS1072E
RoHS, REACH, CMRT

PHYSICAL PROPERTIES

Physical properties	Spec	Value
Operating temperature	-	-60/260°C (-76/500°F)
Short term temperature	-	1200°C (2192°F)
Thermal conductivity	ASTM D1518	0.03 W/mk
Dielectric strength	-	grade A
Flammability	UL 1441 VW-1	pass
Chemical resistance	Resists to chemical and fluids	

DIMENSIONS

Designation*	Indicative nominal Ø (mm)	
	inches	mm
NU-SLEEVE SG-200 HW-B 1/4	1/4"	6
NU-SLEEVE SG-200 HW-B 5/16	5/16"	8
NU-SLEEVE SG-200 HW-B 3/8	3/8"	10
NU-SLEEVE SG-200 HW-B 7/16	7/16"	11
NU-SLEEVE SG-200 HW-B 1/2	1/2"	13
NU-SLEEVE SG-200 HW-B 9/16	9/16"	14
NU-SLEEVE SG-200 HW-B 5/8	5/8"	16
NU-SLEEVE SG-200 HW-B 3/4	3/4"	19
NU-SLEEVE SG-200 HW-B 7/8	7/8"	22
NU-SLEEVE SG-200 HW-B 1	1"	25
NU-SLEEVE SG-200 HW-B 1 1/8	1 1/8"	29
NU-SLEEVE SG-200 HW-B 1 1/4	1 1/4"	32
NU-SLEEVE SG-200 HW-B 1 3/8	1 3/8"	34
NU-SLEEVE SG-200 HW-B 1 1/2	1 1/2"	38
NU-SLEEVE SG-200 HW-B 1 3/4	1 3/4"	45
NU-SLEEVE SG-200 HW-B 2	2"	51
NU-SLEEVE SG-200 HW-B 2 1/4	2 1/4"	57
NU-SLEEVE SG-200 HW-B 2 1/2	2 1/2"	64
NU-SLEEVE SG-200 HW-B 2 3/4	2 3/4"	69
NU-SLEEVE SG-200 HW-B 3	3"	76
NU-SLEEVE SG-200 HW-B 3 1/4	3 1/4"	82
NU-SLEEVE SG-200 HW-B 3 1/2	3 1/2"	88
NU-SLEEVE SG-200 HW-B 3 3/4	3 3/4"	95
NU-SLEEVE SG-200 HW-B 4	4"	101
NU-SLEEVE SG-200 HW-B 4 1/2	4 1/2"	114

* For knitted sleeve designation, replace the HW-B portion by HW-K.

PACKAGING

Coils, Cut lengths upon request